

# Material Safety Data Sheet

## A324 Rapid Release

# Stoner

### 6. ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. If runoff occurs, notify authorities as required.

### 7. HANDLING AND STORAGE

Handling: Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area.  
Storage: Store in a cool, dry, well ventilated area away from all sources of ignition. Empty container may contain residues which are hazardous. Normal precautions common to safe manufacturing practice should be followed in handling and storage.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation is required to maintain operator exposure below published exposure limits. Ventilation should be adequate to prevent exposures above the limits indicated in "Section 2" of this MSDS (from known, suspected or apparent adverse effects).  
Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.  
Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.  
Respiratory Protection: None required for well ventilated situations. A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Vapor Density:	[air = 1] 2.00
Appearance:	Cloudy white	Evaporation Rate:	0.1-0.5 (n-Butyl acetate = 1)
Odor:	Petroleum	Solubility in Water:	Negligible; 0-1%
Specific Gravity:	0.74 @ 70 deg F	Boiling Point:	11 deg F
Vapor Pressure:	2585 mmHg @ 70 deg F	pH:	Not applicable

### 10. STABILITY AND REACTIVITY

Chemical Stability: Stable.  
Conditions to Avoid: Avoid contact with: Strong oxidizing agents. Avoid contact with strong oxidizing agents. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces.  
Decomposition Products: Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various Hydrocarbons.

### 11. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

### 12. TRANSPORTATION INFORMATION

DOT Name:	Aerosols, flammable	UN Number:	UN1950
IATA Name:	Aerosols, flammable	Hazardous Class:	2.1
		Packing Group:	Not applicable

### 13. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.

No components listed in this section. Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.

No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Incorporated, it is the user's obligation to determine the conditions of safe use.

# Material Safety Data Sheet

## A324 Rapid Release

# Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Stoner Incorporated  
1070 Robert Fulton Hwy.  
Quarryville, PA 17566  
1-800-227-5538

Product Name: Rapid Release  
Product Code: A324  
Version Date: 09/28/06  
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	CAS #	ACGIH TLV	OSHA PEL	OTHER
Hydrocarbon propellant	68-476-86-8	800 ppm	None established	None established
NJ Trade Secret Registry	#80100382-5096P	None established	None established	None established
Hydrocarbon solvent	64741-66-8	None	None	196 ppm TWA manuf. recom.
Aliphatic Hydrocarbons	8052-41-3	100 ppm	500 ppm	None established

### 3. HAZARDS IDENTIFICATION

#### POTENTIAL ACUTE [single or short term] HEALTH EFFECTS OF OVEREXPOSURE

**Eye :** May cause eye irritation. Symptoms may include stinging, tearing, and redness.  
**Skin :** Skin contact may cause irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying and cracking, and other skin damage. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.  
**Ingestion :** Swallowing small amounts during handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage.  
**Inhalation :** Inhalation of high concentrations may result in central nervous system (CNS) effects such as dizziness, weakness, fatigue, nausea, headache, and lack of coordination. Breathing large amounts may be harmful. Symptoms are more typically seen at air concentrations exceeding the recommended exposure limits. Symptoms of exposure may include: initial Central Nervous System excitation (euphoria, exhilaration, light-headedness) followed by CNS depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other CNS effects. Confusion, impaired coordination, coma, and death.

#### POTENTIAL CHRONIC [long term] HEALTH EFFECTS OF OVEREXPOSURE:

**General Effects:** Prolonged or repeated exposure can cause drying, defatting, and dermatitis of the skin. Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans.

**Cancer Information:** THIS PRODUCT CONTAINS NO COMPONENTS LISTED AS CARCINOGENIC BY IARC, NTP, OR OSHA 1910(Z)

**Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

#### MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

Respiratory disease including asthma and bronchitis Skin contact may aggravate an existing dermatitis.

#### HAZARDOUS WARNINGS HMIS:

Health: 1 Flammability: 4 Reactivity: 0 Personal Protective Equipment See Section 8

### 4. FIRST AID MEASURES

**Eyes:** Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.  
**Skin Contact:** In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Remove contaminated clothing. Seek medical attention if symptoms persist. Wash clothing before reuse.  
**Ingestion:** Ingestion is an unlikely route of exposure. Do not induce vomiting. Aspiration into the lungs can cause serious damage. Seek medical attention immediately. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Contact a physician, medical facility, or poison control center for advice on whether to induce vomiting.  
**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

#### NOTES TO PHYSICIAN:

This material is an aspiration hazard. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions).

### 5. FIRE FIGHTING MEASURES

**Fire and/or Explosion Hazards:** Extremely Flammable Gas: can readily form explosive air/gas mixture at room temperature or at lower temperatures that are above the flash point. Flammable Liquid: can release vapors that may be ignited at temperatures above or at the flash point. Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point.  
**Fire Fighting Instructions:** Use alcohol foam, water fog, dry chemical, or CO2. Fire fighters should wear normal protective equipment and positive-pressure self-contained breathing apparatus.  
**Aerosol Flame Projection Test:** Extremely flammable aerosol, as determined by ASTM D 3065-94. Do not use near ignition sources such as sparks or open flames.