

# MATERIAL SAFETY DATA SHEET



Date Issued: 01/14/2010  
MSDS No: F-25 PART A

## F-25 PART A

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** F-25 PART A  
**GENERAL USE:** Polyurethane resin  
**CHEMICAL FAMILY:** Aromatic diisocyanate terminated prepolymer

#### MANUFACTURER

BJB Enterprises, Inc.  
14791 Franklin Avenue  
Tustin, CA 92780  
**Customer Service Number:** (714) 734-8450  
**Fax:** (714) 734-8929

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

**CHEMTREC (US Transportation):** (800) 424-9300  
or (703) 527-3887

### 2. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

**PHYSICAL APPEARANCE AND ODOR:** Pale yellow viscous liquid with no odor.

**IMMEDIATE CONCERNS:** May cause eye and skin irritation. Use in well ventilated areas. Avoid breathing vapors. Avoid contact with strong oxidizers and strong acids, as sudden reaction may result in fire and toxic fumes. Reacts slowly with water to produce carbon dioxide which may rupture containers. This reaction accelerates at higher temperatures.

#### POTENTIAL HEALTH EFFECTS

**EYES:** May cause irritation.

**SKIN:** Mild skin irritation.

**INGESTION:** May be harmful if swallowed.

**INHALATION:** May be harmful if inhaled. Inhalation at levels above the occupational exposure limit could cause respiratory sensitization and risk of serious damage to the respiratory system. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitized persons.

**MEDICAL CONDITIONS AGGRAVATED:** None known

**ROUTES OF ENTRY:** Eye and skin contact, inhalation of vapors, or accidental ingestion.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Polypropylene glycol polymer 1,3 diisocyanatomethylbenzene terminated	> 99	9057-91-4
Toluene-2,4-diisocyanate	< 0.1	584-84-9
Toluene-2,6-diisocyanate	< 0.1	91-08-7

### 4. FIRST AID MEASURES

**EYES:** Immediately rinse with water. Remove contact lenses. Hold eyelids apart and flush eyes with water for at least 15 minutes. Get immediate medical attention.

**SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

**INGESTION:** If swallowed, call a physician immediately. Do NOT induce vomiting. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

**INHALATION:** Remove patient from exposure, keep warm and at rest. Obtain immediate medical attention. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is labored, oxygen should be administered by qualified personnel. Apply artificial respiration if breathing has ceased or shows signs of failing.

**NOTES TO PHYSICIAN:** Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

## 5. FIRE FIGHTING MEASURES

**FLASHPOINT AND METHOD:** > 160°C (320°F)

**EXTINGUISHING MEDIA:** Alcohol resistant foam, carbon dioxide, dry chemical, dry sand, or limestone powder.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide, and carbon dioxide.

**FIRE FIGHTING PROCEDURES:** Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

**FIRE FIGHTING EQUIPMENT:** Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

## 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

**LARGE SPILL:** Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

**RELEASE NOTES:** US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

## 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

**HANDLING:** Use appropriate personal protective equipment as specified in Section 8. Handle in a well ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

**STORAGE:** Store in a cool, dry place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

**SHELF LIFE:** 6 months from date of shipment under manufacturers recommended storage conditions.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		SupplierOEL	
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Polypropylene glycol polymer 1,3 diisocyanatomethylbenzene terminated	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
Toluene-2,4-diisocyanate	TWA	NE	NE	(0.005)	NE	NE	NE
	STEL	NE	NE	(0.02)	NE	NE	NE
Toluene-2,6-diisocyanate	TWA	NE	NE	(0.005)	NE	NE	NE
	STEL	NE	NE	(0.02)	NE	NE	NE

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne

levels below recommended exposure limits.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

**SKIN:** Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

**RESPIRATORY:** Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

**PROTECTIVE CLOTHING:** Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

**WORK HYGIENIC PRACTICES:** Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Viscous liquid

**ODOR:** Odorless

**COLOR:** Pale yellow

**pH:** Not Applicable

**PERCENT VOLATILE:** None

**VAPOR PRESSURE:** < 1 mmHg at 21°C (70°F)

**VAPOR DENSITY:** Not Established

**BOILING POINT:** > 250°C (482°F)

**FLASHPOINT AND METHOD:** > 160°C (320°F)

**SOLUBILITY IN WATER:** Reacts slowly with water

**SPECIFIC GRAVITY:** 1.050 (water=1) at 25°C (77°F)

**VISCOSITY:** 3700 Centipoise at 25°C (77°F)

**VOC (Volatile Organic Compound):** None

## 10. STABILITY AND REACTIVITY

**STABILITY:** This product is stable under normal ambient conditions of temperature and pressure.

**POLYMERIZATION:** Product may foam when exposed to heat and moisture.

**CONDITIONS TO AVOID:** High temperatures, moisture, and freezing conditions.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide and carbon dioxide.

**INCOMPATIBLE MATERIALS:** Moisture, oxidizing agents, and alcohols.

## 11. TOXICOLOGICAL INFORMATION

### TOXICITY TO ANIMALS

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
Polypropylene glycol polymer 1,3 diisocyanatomethylbenzene terminated	Not Established	Not Established	Not Established
Toluene-2,4-diisocyanate	> 5000 mg/kg	> 4000 mg/kg	> 480 mg/kg
Toluene-2,6-diisocyanate	> 5000 mg/kg	> 4000 mg/kg	> 480 mg/kg

**CARCINOGENICITY**

Chemical Name	NTP Status	IARC Status
Toluene-2,4-diisocyanate	2	2B
Toluene-2,6-diisocyanate	2	2B

**IARC:** This product contains substances that are classified as possible carcinogens to humans.

**12. ECOLOGICAL INFORMATION**

**ECOTOXICOLOGICAL INFORMATION:** No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.

**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** The generation of waste should be avoided or minimized wherever possible. Disposal should be in accordance with local, state, provincial or national regulations.

**EMPTY CONTAINER:** Containers must be emptied (as defined by RCRA, 40 CFR Section 261.7 or state regulations that may be more stringent) and either passed to an approved recycler or destroyed.

**14. TRANSPORT INFORMATION****DOT (DEPARTMENT OF TRANSPORTATION) LAND**

**NOTE:** Not Regulated

**AIR (ICAO/IATA):** Not Regulated

**VESSEL (IMO/IMDG):** Not Regulated

**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

**311/312 HAZARD CATEGORIES:** None

**313 REPORTABLE INGREDIENTS:** This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

**EPCRA SECTION 313 SUPPLIER NOTIFICATION**

Chemical Name	Wt. %	CAS
Toluene-2,4-diisocyanate	< 0.1	584-84-9
Toluene-2,6-diisocyanate	< 0.1	91-08-7

**CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)**

**CERCLA REGULATORY:** For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675):

Chemical Name	Wt. %	CERCLA RQ
Toluene-2,4-diisocyanate	< 0.1	100 lbs.
Toluene-2,6-diisocyanate	< 0.1	100 lbs.

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

**TSCA STATUS:** This product or its components are listed in or exempt from the TSCA inventory requirements.

**CLEAN AIR ACT**

Chemical Name	Wt. %	CAS
Toluene-2,4-diisocyanate	< 0.1	584-84-9
Toluene-2,6-diisocyanate	< 0.1	91-08-7

#### OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

**29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS:** None of the chemicals in this product are considered highly hazardous by OSHA.

#### REGULATIONS

**STATE REGULATIONS:** California Proposition 65: This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

#### CALIFORNIA PROPOSITION 65

Chemical Name	Wt. %	Listed
Toluene-2,4-diisocyanate	< 0.1	Cancer
Toluene-2,6-diisocyanate	< 0.1	Cancer

**OSHA HAZARD COMM. RULE:** The contents of the MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### 16. OTHER INFORMATION

**REASON FOR ISSUE:** Revised format


**APPROVED BY:** Michael Rose    **TITLE:** R & D Manager

**PREPARED BY:** Gus Alidad

#### HMIS RATING

<b>HEALTH:</b>	<b>1</b>
<b>FLAMMABILITY:</b>	<b>1</b>
<b>PHYSICAL HAZARD:</b>	<b>1</b>
<b>PERSONAL PROTECTION:</b>	<b>X</b>

#### NFPA CODES



**HMIS RATINGS NOTES:** Personal Protection: See Section 8

**MANUFACTURER DISCLAIMER:** This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.