

# MATERIAL SAFETY DATA SHEET



**Date Issued:** 02/01/2007  
**MSDS No:** F-90 PART A  
**Date-Revised:** 03/28/2011  
**Revision No:** 1

## F-90 PART A

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** F-90 PART A

**GENERAL USE:** Polyurethane resin

**CHEMICAL FAMILY:** Diisocyanate terminated polyglycols in plasticizer/paraffin mixture

#### MANUFACTURER

BJB Enterprises, Inc.

14791 Franklin Avenue

Tustin, CA 92780

**Emergency Phone:** (714) 734-8450

**Fax:** (714) 734-8929

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

**CHEMTREC (US Transportation):** (800) 424-9300

or (703) 527-3887

### 2. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

**PHYSICAL APPEARANCE AND ODOR:** Pale yellow viscous liquid with a slight aromatic hydrocarbon odor.

**IMMEDIATE CONCERNS:** May cause eye and skin irritation. Use in well ventilated areas. Avoid breathing vapors. Avoid contact with strong oxidizers and strong acids, as sudden reaction may result in fire and toxic fumes. Reacts slowly with water to produce carbon dioxide which may rupture containers. This reaction accelerates at higher temperatures.

#### POTENTIAL HEALTH EFFECTS

**EYES:** May cause irritation, tearing, reddening, and swelling.

**SKIN:** May cause irritation and possible allergic sensitivity. Skin inflammation is characterized by itching, scaling, or reddening.

**INGESTION:** May be harmful if swallowed.

**INHALATION:** May be harmful if inhaled. Inhalation at levels above the occupational exposure limit could cause respiratory sensitization and risk of serious damage to the respiratory system. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitized persons.

**MEDICAL CONDITIONS AGGRAVATED:** May cause or aggravate dermatitis and asthma.

**ROUTES OF ENTRY:** Eye and skin contact, inhalation of vapors, or accidental ingestion.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

**F-90 PART A**

Chemical Name	Wt. %	CAS
Polytetramethylene glycol polymer 1,3 diisocyanatomethylbenzene terminated	40 - 60	Proprietary
Polypropylene glycol polymer 1,3 diisocyanatomethylbenzene terminated	20 - 40	Proprietary
Chlorinated paraffins	5 - 10	63449-39-8
Dibutyl phthalate	1 - 5	84-74-2
Aromatic hydrocarbon	< 2.5	64742-94-5
Naphthalene	< 0.25	91-20-3
Toluene Diisocyanate	< 0.03	26471-62-5
Toluene-2,6-diisocyanate	< 0.02	91-08-7
Toluene-2,4-diisocyanate	< 0.02	584-84-9

**4. FIRST AID MEASURES**

**EYES:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult a physician.

**SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

**INGESTION:** If swallowed, call a physician immediately. Do NOT induce vomiting. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

**INHALATION:** Remove patient from exposure, keep warm and at rest. Obtain immediate medical attention. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is labored, oxygen should be administered by qualified personnel. Apply artificial respiration if breathing has ceased or shows signs of failing.

**NOTES TO PHYSICIAN:** Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

**5. FIRE FIGHTING MEASURES**

**FLASHPOINT AND METHOD:** 110°C (230°F) Pinsky-Martens CC

**EXTINGUISHING MEDIA:** Water spray, carbon dioxide, dry chemical, or alcohol foam.

**EXPLOSION HAZARDS:** Avoid contact with strong oxidizers and strong acids, as sudden reaction may result in fire and toxic fumes. Reacts slowly with water to produce carbon dioxide which may rupture closed containers. This reaction accelerates at higher temperatures.

**FIRE FIGHTING PROCEDURES:** Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

**FIRE FIGHTING EQUIPMENT:** Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

**6. ACCIDENTAL RELEASE MEASURES**

**SMALL SPILL:** Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

**LARGE SPILL:** Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

**RELEASE NOTES:** US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

**7. HANDLING AND STORAGE**

**GENERAL PROCEDURES:** Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over

**F-90 PART A**

open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

**HANDLING:** Use appropriate personal protective equipment as specified in Section 8. Handle in a well ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

**STORAGE:** Store in a cool, dry place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

**SHELF LIFE:** 6 months from date of shipment under manufacturers recommended storage conditions.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Polytetramethylene glycol polymer 1,3 diisocyanatomethylbenzene terminated	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
Polypropylene glycol polymer 1,3 diisocyanatomethylbenzene terminated	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
Chlorinated paraffins	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
Dibutyl phthalate	TWA	NE	5	NE	5	NE <sup>[1]</sup>	5 <sup>[1]</sup>
	STEL	NE	NE	NE	NE	NE	NE
Aromatic hydrocarbon	TWA	NE	NE	NE	NE	17	100
	STEL	NE	NE	NE	NE	NE	NE
Naphthalene	TWA	10	50	10	52	10 <sup>[1]</sup>	50 <sup>[1]</sup>
	STEL	NE	NE	15	79	15	75
Toluene Diisocyanate	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
Toluene-2,6-diisocyanate	TWA	NE	NE	(0.005)	NE	NE	NE
	STEL	NE	NE	(0.02)	NE	NE	NE
Toluene-2,4-diisocyanate	TWA	NE	NE	(0.005)	NE	NE	NE
	STEL	NE	NE	(0.02)	NE	NE	NE
<b>OSHA TABLE COMMENTS:</b>							
1. NIOSH REL							

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

**SKIN:** Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

**RESPIRATORY:** Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved)

**F-90 PART A**

may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

**PROTECTIVE CLOTHING:** Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

**WORK HYGIENIC PRACTICES:** Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**PHYSICAL STATE:** Viscous liquid

**ODOR:** Slight aromatic hydrocarbon

**APPEARANCE:** Clear

**COLOR:** Pale yellow

**pH:** Not Applicable

**PERCENT VOLATILE:** 2.2

**VAPOR PRESSURE:** < 1 mmHg at 21°C (70°F)

**VAPOR DENSITY:** Not Established

**BOILING POINT:** > 250°C (482°F)

**FLASHPOINT AND METHOD:** 110°C (230°F) Pensky-Martens CC

**SOLUBILITY IN WATER:** Reacts slightly with water

**SPECIFIC GRAVITY:** 1.090 (water=1) at 25°C (77°F)

**VISCOSITY:** 6000 Centipoise at 25°C (77°F)

**VOC (Volatile Organic Compound):** 24.000 g/l Calculated. Theoretical VOC minus water and exempt solvents.

**10. STABILITY AND REACTIVITY**

**STABILITY:** This product is stable under normal ambient conditions of temperature and pressure.

**POLYMERIZATION:** Product may foam when exposed to heat and moisture.

**CONDITIONS TO AVOID:** High temperatures, moisture, and freezing conditions.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, nitrous oxide, and HCN.

**INCOMPATIBLE MATERIALS:** Moisture, strong acids, amines, and metal carboxylates.

**11. TOXICOLOGICAL INFORMATION****TOXICITY TO ANIMALS**

**F-90 PART A**

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
Polytetramethylene glycol polymer 1,3 diisocyanatomethylbenzene terminated	Not Established	Not Established	Not Established
Polypropylene glycol polymer 1,3 diisocyanatomethylbenzene terminated	Not Established	Not Established	Not Established
Chlorinated paraffins	> 4 g/kg	Not Established	Not Established
Dibutyl phthalate	20000 to 25000 mg/kg	> 20960 mg/kg	Not Established
Aromatic hydrocarbon	Not Established	> 2000 mg/kg	Not Established
Naphthalene	490 mg/kg	> 20 g/kg	Not Established
Toluene Diisocyanate	Not Established	Not Established	Not Established
Toluene-2,6-diisocyanate	> 5000 mg/kg	> 4000 mg/kg	> 480 mg/kg
Toluene-2,4-diisocyanate	> 5000 mg/kg	> 4000 mg/kg	> 480 mg/kg

**CARCINOGENICITY**

Chemical Name	NTP Status	IARC Status
Naphthalene	2	2B
Toluene-2,6-diisocyanate	2	2B
Toluene-2,4-diisocyanate	2	2B

**IARC:** This product contains substances that are classified as possible carcinogens to humans.

**NTP:** Potential for exposure to the substances listed.

**12. ECOLOGICAL INFORMATION**

**ECOTOXICOLOGICAL INFORMATION:** No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.

**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** The generation of waste should be avoided or minimized wherever possible. Disposal should be in accordance with local, state, provincial or national regulations.

**EMPTY CONTAINER:** Containers must be emptied (as defined by RCRA, 40 CFR Section 261.7 or state regulations that may be more stringent) and either passed to an approved recycler or destroyed.

**14. TRANSPORT INFORMATION****DOT (DEPARTMENT OF TRANSPORTATION) LAND**

**PROPER SHIPPING NAME:** Environmentally hazardous substances, liquid, n.o.s. (See Note)

**TECHNICAL NAME:** (dibutyl phthalate)

**PRIMARY HAZARD CLASS/DIVISION:** 9

**UN/NA NUMBER:** UN 3082

**PACKING GROUP:** III

**REPORTABLE QUANTITY (RQ) UNDER CERCLA:** 10 lb of dibutyl phthalate

**LABEL:** Class 9 (miscellaneous hazardous materials)

**NOTE:** Applies ONLY to containers with a RQ of dibutyl phthalate (10 lb), otherwise not regulated.

**AIR (ICAO/IATA)**

**SHIPPING NAME:** Environmentally hazardous substances, liquid, n.o.s. (See Note)

**F-90 PART A****TECHNICAL NAME:** (dibutyl phthalate)**UN/NA NUMBER:** UN 3082**PRIMARY HAZARD CLASS/DIVISION:** 9**PACKING GROUP:** III**LABEL:** Class 9 (miscellaneous hazardous materials)**NOTE:** Applies ONLY to containers with a RQ of dibutyl phthalate (10 lb), otherwise not regulated.**VESSEL (IMO/IMDG)****SHIPPING NAME:** Environmentally hazardous substance, liquid, n.o.s.**TECHNICAL NAME:** (dibutyl phthalate)**UN/NA NUMBER:** UN 3082**PRIMARY HAZARD CLASS/DIVISION:** 9**PACKING GROUP:** III**LIMITED QUANTITY:** 5 liters**MARINE POLLUTANT #1:** Yes (dibutyl phthalate)**LABEL:** Class 9 (miscellaneous hazardous materials)**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****311/312 HAZARD CATEGORIES:** None**313 REPORTABLE INGREDIENTS:** This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:**EPCRA SECTION 313 SUPPLIER NOTIFICATION**

Chemical Name	Wt. %	CAS
Dibutyl phthalate	1 - 5	84-74-2

**CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)****CERCLA REGULATORY:** For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675):

Chemical Name	Wt. %	CERCLA RQ
Dibutyl phthalate	1 - 5	10 lbs.
Naphthalene	< 0.25	100 lbs.
Toluene Diisocyanate	< 0.03	100
Toluene-2,6-diisocyanate	< 0.02	100 lbs.
Toluene-2,4-diisocyanate	< 0.02	100 lbs.

**TSCA (TOXIC SUBSTANCE CONTROL ACT)****TSCA REGULATORY:** This product contains naphthalene which is subject to TSCA Section 12(b) export notification.**TSCA STATUS:** This product or its components are listed in or exempt from the TSCA inventory requirements.**CLEAN AIR ACT**

Chemical Name	Wt. %	CAS
Toluene Diisocyanate	< 0.03	26471-62-5
Toluene-2,6-diisocyanate	< 0.02	91-08-7
Toluene-2,4-diisocyanate	< 0.02	584-84-9

**F-90 PART A****OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)**

**29 CFR1910.119--PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS:** None of the chemicals in this product are considered highly hazardous by OSHA.

**REGULATIONS**

**STATE REGULATIONS:** California Proposition 65: This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

**CALIFORNIA PROPOSITION 65**

Chemical Name	Wt. %	Listed
Dibutyl phthalate	1 - 5	<ul style="list-style-type: none"> <li>● Cancer</li> <li>● Developmental Toxicity</li> <li>● Female Reproductive</li> <li>● Male Reproductive</li> </ul>
Naphthalene	< 0.25	Cancer
Toluene Diisocyanate	< 0.03	Cancer

**OSHA HAZARD COMM. RULE:** The contents of the MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**CANADA**

**WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):** This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

**WHMIS CLASS:** B4, D2A

**DOMESTIC SUBSTANCE LIST (INVENTORY):** All components in this product are included on the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

**16. OTHER INFORMATION**

**REASON FOR ISSUE:** Revision


**APPROVED BY:** Michael Rose    **TITLE:** R & D Manager

**PREPARED BY:** Gus Alidad

**REVISION SUMMARY:** This MSDS replaces the 02/01/2007 MSDS. Revised: **Section 1:** REASON FOR ISSUE. **Section 15:** CERCLA REGULATORY, WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM), 40 CFR PART 68--- RISK MANAGEMENT FOR CHEMICAL ACCIDENT RELEASE PREVENTION, WHMIS CLASS.

**HMIS RATING**

<b>HEALTH</b>	<input type="checkbox"/>	<b>1</b>
<b>FLAMMABILITY</b>	<input type="checkbox"/>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<input type="checkbox"/>	<b>1</b>
<b>PERSONAL PROTECTION</b>	<input checked="" type="checkbox"/>	

**NFPA CODES**

**HMIS RATINGS NOTES:** Personal Protection: See Section 8

**MANUFACTURER DISCLAIMER:** This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.