

Material Safety Data Sheet

TC-1606 PART A

Date of Preparation: 08/05/2005

Revision: 08/05/2005

Section 1 - Chemical Product and Company Identification

Product Name: TC-1606 PART A

Product Class: Epoxy resin solution

Chemical Type: Bisphenol A diglycidyl ether resin solution in glycol ester

Manufacturer: BJB Enterprises, Inc., 14791 Franklin Avenue, Tustin, CA 92780, Phone (714) 734-8450, Fax (714) 734-8929, (M-Th: 8-4:30, F: 7:30-4), Emergency Phone: Chemtrec (800) 424-9300 or (703) 527-3887

Section 2 - Composition / Information on Ingredients

Ingredient Name	CASRN	% wt
1. Bisphenol A diglycidyl ether resin	25068-38-6	90-100
2. Glycol ether acetate	108-65-6	5-10

Section 3 - Hazards Identification

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Appearance: Black liquid ; Odor: sweet; Avoid skin contact. Avoid breathing vapors. May cause eye and skin irritation. Harmful if inhaled. Use in well-ventilated areas. Burning material will generate toxic combustion products.

HMIS

H 2

F 2

R 0

PPE†

†Sec. 8

Potential Health Effects

Primary Entry Routes: Eye and skin contact; inhalation of vapors, accidental ingestion.

Inhalation/Ingestion: Respiratory irritation may be moderately toxic/May cause gastric irritation.

Eye: May cause irritation and redness.

Skin: May cause irritation and allergic skin reaction.

Medical Conditions Aggravated by Long-Term Exposure: None known

Section 4 - First Aid Measures

Inhalation: Not likely. Remove to fresh air environment.

Ingestion: If swallowed, call a physician immediately. Remove stomach contents by gastric suction or induce vomiting only as directed by medical personnel. Never give anything by mouth to an unconscious person.

Eye Contact: Flush eyes with clean, lukewarm water for 15 minutes. Obtain medical attention if irritation develops.

Skin Contact: Remove contaminated clothing and wash affected areas well with soap and water. Launder contaminated clothing before use.

Note to Physicians: Treat any ill effects symptomatically.

Section 5 - Fire-Fighting Measures

Flash Point/Method: 146°F (63°C) PMCC


Extinguishing Media: CO₂, Foam, water or dry chemical extinguisher.

Unusual Fire or Explosion Hazards: Generates toxic combustion products.

Fire-Fighting Instructions: Cool fire exposed containers with water spray. Remove containers from fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

NFPA



Section 6 - Accidental Release Measures

Spill /Leak Procedures: Provide adequate ventilation and wear personal protective equipment. Evacuate personnel as a precaution. Prevent product spill from entering sewers, streams, or drinking water supplies. Collect liquid or soak up with inert filler or an absorbent, such as dry earth, sand, or oil absorbent (sweeping) compound. Collect material into suitable containers for disposal. Wash area with dilute ammonia solution.

Containment: For large spills, dike ahead of liquid spill for later neutralization, absorption, clean up, and disposal.

Section 7 - Handling and Storage

Handling Precautions: Avoid contact with eyes, skin and clothing. Avoid breathing vapor over open container.

Storage Temperature: 65° - 85°F (18° - 29°C)

Storage Requirements: Store in a cool, dry place away from excessive heat in original or similar waterproof containers. Avoid unnecessary contact. Combustible. Store away from ignition sources or high heat. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

Shelf life: 12 months from date of shipment under manufacturers recommended storage conditions.

Section 8 - Exposure Controls / Personal Protection

Exposure Limits:

Bisphenol A diglycidyl ether resin (25068-38-6):

Not established

Glycol ether acetate (108-65-6):

Not established

Eye Protection Requirements: Safety goggles or glasses are recommended. Plastic face shield should be worn for complete face protection.

Skin Protection Requirements: Impermeable gloves should be worn. Employees should wash their hands and face before eating, drinking, or using tobacco products.

Ventilation/Respiratory Requirements: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH certified) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Additional Protective Measures: Safety showers and eye wash stations should be easily accessible to the work area. Training is important. Follow all label precautions.

Section 9 - Physical and Chemical Properties

Flash Point/Method: 146°F (63°C) PMCC

Physical State: Liquid

Appearance and Odor: Black; sweet odor

Vapor Pressure: <4 mm Hg at 68°F (20°C)

Specific Gravity (H₂O=1): 1.18

pH: N/A

Water Solubility: slight

Boiling Point: >300°F (149°C)

Viscosity: 1,300 cps

% Volatile: 8

V.O.C. (ref EPA meth 24): 94 g/l

Section 10 - Stability and Reactivity

Stability: Stable at room temperature in closed containers under normal storage and handling conditions.

Hazardous Polymerization: Will not occur.

Chemical Incompatibilities/Conditions to Avoid: Strong oxidizing agents, mineral acids and high heat.

Hazardous Decomposition: Thermal oxidative decomposition can produce toxic combustion products.

Section 11- Toxicological Information

Animal Toxicity:

Bisphenol A diglycidyl ether resin (25068-38-6):

LD50 Oral (rat): 5,000 mg/kg

LD50 Dermal (rabbit): >6,000 mg/kg

Glycol ether acetate (108-65-6):

LD50 Oral (rat): >10,000 mg/kg

LD50 Dermal (rabbit): >5,000 mg/kg

Section 12 - Ecological Information

Ecotoxicity:

Bisphenol A diglycidyl ether resin (25068-38-6):

LC50 Rainbow trout: 1.5 mg/l (96 h)

LC50 Zebra Fish: 2.4 mg/l (96 h)

EC50 Daphnia Magna: 3.6 mg/l (24 h)

Glycol ether acetate (108-65-6):

LC50 Fathead Minnow: 161 mg/l (96 h)

LC50 Daphnia Magna: 408 mg/l (48 h)

Section 13 - Disposal Considerations

Waste Disposal Method: Incinerate or approved landfill burial unless prohibited. Dispose of in compliance with federal, state, or local environmental control regulations.

Section 14 - Transport Information

DOT
Not regulated

IATA/ICAO
Not regulated

IMO/IMDG
Not regulated

Section 15 - Regulatory Information**U.S. Federal Regulations:****OSHA:**

This document has been prepared in accordance with the MSDS requirements of the OSHA Hazard Communication Standard.

SARA TITLE III:

Sections 311/312 Hazard Classification:

Acute health hazard

Section 313: This product contains the following substances subject to the reporting requirements of EPCRA, Section 313 and 40 CFR Part 372:

None

TSCA: This product or its components are listed in or exempt from the TSCA inventory requirements.

This product contains the following substances subject to export notification under Section 12 (b) of TSCA:

None

State Regulations:

California Proposition 65: This product contains the following substances known to the State of California to cause cancer and/or cause birth defects or other reproductive harm:

None

Section 16 - Other Information

Reason for Issue: Revised Section 2, 3, 5, 8, 9, 11, 12, 14, & 15

Prepared By: G. Alidad

Approval Date: 08/05/2005

Supersedes Date: 04/09/02001

Disclaimer: This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon these data.