

# MATERIAL SAFETY DATA SHEET



Date Issued: 11/18/2011  
MSDS No: TC-850 PART A

## TC-850 PART A

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** TC-850 PART A  
**GENERAL USE:** Polyurethane resin  
**CHEMICAL FAMILY:** Aromatic diisocyanate

#### MANUFACTURER

BJB Enterprises, Inc.  
14791 Franklin Avenue  
Tustin, CA 92780

**Customer Service Number:** (714) 734-8450

**Fax:** (714) 734-8929

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

**CHEMTREC (US Transportation):** (800) 424-9300  
or (703) 527-3887

### 2. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

**PHYSICAL APPEARANCE AND ODOR:** Pale yellow liquid with a slight musty odor.

**IMMEDIATE CONCERNS:** Avoid eye and skin contact. Avoid breathing vapors. May cause eye and skin irritation. Use in well ventilated areas. Reacts slowly with water to produce carbon dioxide which may rupture closed containers. This reaction accelerates at higher temperatures. Inhalation at levels above the occupational exposure limit could cause respiratory sensitization and risk of serious damage to respiratory system. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitized persons.

#### POTENTIAL HEALTH EFFECTS

**EYES:** May cause irritation, tearing, reddening, and swelling.

**SKIN:** May cause irritation and possible allergic sensitivity. Skin inflammation is characterized by itching, scaling, or reddening.

**INGESTION:** Slightly hazardous in case of ingestion.

**INHALATION:** Hazardous in case of inhalation (lung irritant, lung sensitizer).

**MEDICAL CONDITIONS AGGRAVATED:** May cause or aggravate dermatitis and asthma.

**ROUTES OF ENTRY:** Eye and skin contact, inhalation of vapors, or accidental ingestion.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
4,4'-Diphenylmethane diisocyanate	40 - 50	101-68-8
Diisodecyl Phthalate (DIDP)	30 - 40	68515-49-1
Modified MDI	10 - 20	Proprietary

### 4. FIRST AID MEASURES

**EYES:** Immediately rinse with water. Remove contact lenses. Hold eyelids apart and flush eyes with water for at least 15 minutes. Get immediate medical attention.

**SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

**INGESTION:** If swallowed, call a physician immediately. Do NOT induce vomiting. Provided the patient is conscious, wash out mouth with

**TC-850 PART A**

water. Never give anything by mouth to an unconscious person.

**INHALATION:** Remove patient from exposure, keep warm and at rest. Obtain immediate medical attention. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is labored, oxygen should be administered by qualified personnel. Apply artificial respiration if breathing has ceased or shows signs of failing.

**NOTES TO PHYSICIAN:** Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

**5. FIRE FIGHTING MEASURES**

**FLASHPOINT AND METHOD:** 207°C (405°F) Pinsky-Martens CC

**EXTINGUISHING MEDIA:** Water spray, carbon dioxide, dry chemical, or alcohol foam.

**EXPLOSION HAZARDS:** Avoid contact with strong oxidizers and strong acids, as sudden reaction may result in fire and toxic fumes. Reacts slowly with water to produce carbon dioxide which may rupture closed containers. This reaction accelerates at higher temperatures.

**FIRE FIGHTING PROCEDURES:** Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

**FIRE FIGHTING EQUIPMENT:** Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

**6. ACCIDENTAL RELEASE MEASURES**

**SMALL SPILL:** Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

**LARGE SPILL:** Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

**RELEASE NOTES:** US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

**7. HANDLING AND STORAGE**

**GENERAL PROCEDURES:** Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

**HANDLING:** Use appropriate personal protective equipment as specified in Section 8. Handle in a well ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

**STORAGE:** Store in a cool, dry place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

**SHELF LIFE:** 6 months from date of shipment under manufacturers recommended storage conditions.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

## TC-850 PART A

## EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		SupplierOEL	
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
4,4'-Diphenylmethane diisocyanate	TWA	0.02	0.2	0.005	0.05	0.005 <sup>[1]</sup>	0.05 <sup>[1]</sup>
	STEL	NE	NE	NE	NE	NE	NE
Diisodecyl Phthalate (DIDP)	TWA	NE	NE	NE	NE	NE	5 mg/m3
	STEL	NE	NE	NE	NE	NE	NE
Modified MDI	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
<b>OSHA TABLE COMMENTS:</b>							
1. NIOSH REL							

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

**PERSONAL PROTECTIVE EQUIPMENT**

**EYES AND FACE:** Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

**SKIN:** Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

**RESPIRATORY:** Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

**PROTECTIVE CLOTHING:** Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

**WORK HYGIENIC PRACTICES:** Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**PHYSICAL STATE:** Liquid

**ODOR:** Slightly musty

**COLOR:** Pale yellow

**pH:** Not Applicable

**PERCENT VOLATILE:** 0.03

**VAPOR PRESSURE:** < 0.1 mmHg at 25°C (77°F)

**VAPOR DENSITY:** Heavier than air

**BOILING POINT:** > 250°C (482°F) Decomposes

**FLASHPOINT AND METHOD:** 207°C (405°F) Pensky-Martens CC

**SOLUBILITY IN WATER:** Reacts slowly with water

**SPECIFIC GRAVITY:** 1.100 (water=1) at 25°C (77°F)

**VISCOSITY:** 75 Centipoise at 25°C (77°F)

**VOC (Volatile Organic Compound):** < 0.330 g/l Calculated. Theoretical VOC minus water and exempt solvents.

**TC-850 PART A****10. STABILITY AND REACTIVITY**

**STABILITY:** This product is stable under normal ambient conditions of temperature and pressure.

**POLYMERIZATION:** May occur when exposed to heat in the presence of moisture, alkalis, tertiary amines, metal compounds.

**CONDITIONS TO AVOID:** High temperatures, moisture, and freezing conditions.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, nitrous oxide, and HCN.

**INCOMPATIBLE MATERIALS:** Avoid contact with any materials containing active hydrogens such as water, alcohol, amines, bases, and acids.

**11. TOXICOLOGICAL INFORMATION****TOXICITY TO ANIMALS**

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
4,4'-Diphenylmethane diisocyanate	> 5000 mg/kg	> 5000 mg/kg	2240 mg/m <sup>3</sup> (1 h of respirable aerosol)
Diisodecyl Phthalate (DIDP)	> 10 g/kg	> 3.16 g/kg	> 0.13 mg/l
Modified MDI	Not Established	Not Established	Not Established

**CARCINOGENICITY**

Chemical Name	IARC Status
4,4'-Diphenylmethane diisocyanate	3

**IARC:** This product contains substances that are not classifiable as carcinogens to humans.

**12. ECOLOGICAL INFORMATION****AQUATIC TOXICITY**

**96-HOUR LC<sub>50</sub>:** > 1000 mg/l Fish

**48-HOUR EC<sub>50</sub>:** > 1000 mg/l Daphnia magna

**Notes:** This information is based only on MDI and its derivatives.

**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** The generation of waste should be avoided or minimized wherever possible. Disposal should be in accordance with local, state, provincial or national regulations.

**EMPTY CONTAINER:** Containers must be emptied (as defined by RCRA, 40 CFR Section 261.7 or state regulations that may be more stringent) and either passed to an approved recycler or destroyed.

**14. TRANSPORT INFORMATION****DOT (DEPARTMENT OF TRANSPORTATION) LAND**

**NOTE:** Not Regulated

**AIR (ICAO/IATA):** Not Regulated

**VESSEL (IMO/IMDG):** Not Regulated

**15. REGULATORY INFORMATION****UNITED STATES**

**SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

**TC-850 PART A**

**311/312 HAZARD CATEGORIES:** Acute health hazard. Chronic health hazard

**313 REPORTABLE INGREDIENTS:** This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

**EPCRA SECTION 313 SUPPLIER NOTIFICATION**

Chemical Name	Wt. %	CAS	Comments
4,4'-Diphenylmethane diisocyanate	40 - 50	101-68-8	Diisocyanate Compounds (Category Code N120)

**CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)**

**CERCLA REGULATORY:** For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675):

Chemical Name	Wt. %	CERCLA RQ
4,4'-Diphenylmethane diisocyanate	40 - 50	5,000 lbs.

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

**TSCA STATUS:** This product or its components are listed in or exempt from the TSCA inventory requirements.

**OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)**

**29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS:** None of the chemicals in this product are considered highly hazardous by OSHA.

**REGULATIONS**

**STATE REGULATIONS:** California Proposition 65: This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

**CALIFORNIA PROPOSITION 65**

Chemical Name	Wt. %	Listed
Diisodecyl Phthalate (DIDP)	30 - 40	<ul style="list-style-type: none"> <li>● Cancer</li> <li>● Developmental Toxicity</li> </ul>

**OSHA HAZARD COMM. RULE:** The contents of the MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**CANADA****WHMIS HAZARD SYMBOL AND CLASSIFICATION**

Toxic

Class D-1A: Material causing immediate and serious toxic effects (Very toxic).

Class D-2A: Material causing other toxic effects (Very toxic).

Class D-2B: Material causing other toxic effects (Toxic).

**WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):** This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

**WHMIS CLASS:** The D1A classification applies to methylene bisphenyl isocyanate aerosol. No LC50 values for the vapour were located. The vapour pressure of this material is very low.

**DOMESTIC SUBSTANCE LIST (INVENTORY):** All components in this product are included on the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

**EUROPEAN COMMUNITY**

**TC-850 PART A****EEC LABEL SYMBOL AND CLASSIFICATION**

"Xn" - Harmful

**RISK PHRASES**

R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R40: Limited evidence of a carcinogenic effect.

R42/43: May cause sensitization by inhalation and skin contact.

R48/20: Harmful : danger of serious damage to health by prolonged exposure through inhalation.

**SAFETY PHRASES**

S1/2: Keep locked up and out of reach of children.


S23: Do not breathe fumes/vapour/spray.

S36/37: Wear suitable protective clothing and gloves.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

**16. OTHER INFORMATION****REASON FOR ISSUE:** Revised format**APPROVED BY:** Michael Rose    **TITLE:** R & D Manager**PREPARED BY:** Gus Alidad**HMIS RATING**

<b>HEALTH</b>	*	<b>2</b>
<b>FLAMMABILITY</b>		<b>1</b>
<b>PHYSICAL HAZARD</b>		<b>1</b>
<b>PERSONAL PROTECTION</b>		<b>X</b>

**NFPA CODES****HMIS RATINGS NOTES:** Personal Protection: See Section 8

**MANUFACTURER DISCLAIMER:** This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.