

MATERIAL SAFETY DATA SHEET



Date Issued: 07/29/2009
MSDS No: TC-852 PART A

TC-852 PART A

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: TC-852 PART A
GENERAL USE: Polyurethane resin
CHEMICAL FAMILY: Aromatic diisocyanate

MANUFACTURER

BJB Enterprises, Inc.
14791 Franklin Avenue
Tustin,, CA 92780
Customer Service Number: (714) 734-8450
Fax: (714) 734-8929

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300
or (703) 527-3887

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE AND ODOR: Yellow liquid with a slight odor.

IMMEDIATE CONCERNS: May cause eye and skin irritation. Use in well ventilated areas. Avoid breathing vapors. Avoid contact with strong oxidizers and strong acids, as sudden reaction may result in fire and toxic fumes. Reacts slowly with water to produce carbon dioxide which may rupture containers. This reaction accelerates at higher temperatures.

POTENTIAL HEALTH EFFECTS

EYES: May cause irritation, tearing, reddening, and swelling.

SKIN: May cause irritation and possible allergic sensitivity. Skin inflammation is characterized by itching, scaling, or reddening.

INGESTION: Slightly hazardous in case of ingestion.

INHALATION: May be harmful if inhaled. Inhalation at levels above the occupational exposure limit could cause respiratory sensitization and risk of serious damage to the respiratory system. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitized persons.

MEDICAL CONDITIONS AGGRAVATED: May cause or aggravate dermatitis and asthma.

ROUTES OF ENTRY: Eye and skin contact, inhalation of vapors, or accidental ingestion.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
4,4'-Diphenylmethane diisocyanate	40 - 50	101-68-8
1,2-Benzenedicarboxylic acid	30 - 40	68515-49-1
Modified MDI	10 - 20	Proprietary

4. FIRST AID MEASURES

EYES: Immediately rinse with water. Remove contact lenses. Hold eyelids apart and flush eyes with water for at least 15 minutes. Get immediate medical attention.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

INGESTION: If swallowed, call a physician immediately. Do NOT induce vomiting. Provided the patient is conscious, wash out

mouth with water. Never give anything by mouth to an unconscious person.

INHALATION: Remove patient from exposure, keep warm and at rest. Obtain immediate medical attention. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is labored, oxygen should be administered by qualified personnel. Apply artificial respiration if breathing has ceased or shows signs of failing.

NOTES TO PHYSICIAN: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: 193°C (380°F) Pinsky-Martens CC

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical, or alcohol foam.

EXPLOSION HAZARDS: Avoid contact with strong oxidizers and strong acids, as sudden reaction may result in fire and toxic fumes. Reacts slowly with water to produce carbon dioxide which may rupture closed containers. This reaction accelerates at higher temperatures.

FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

FIRE FIGHTING EQUIPMENT: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

LARGE SPILL: Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

RELEASE NOTES: US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

HANDLING: Use appropriate personal protective equipment as specified in Section 8. Handle in a well ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

STORAGE: Store in a cool, dry place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

SHELF LIFE: 6 months from date of shipment under manufacturers recommended storage conditions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		SupplierOEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
4,4'-Diphenylmethane diisocyanate	TWA	NE	NE	0.005	0.051	0.005 ^[1]	0.05 ^[1]
	STEL	NE	NE	NE	NE	NE	NE
1,2-Benzenedicarboxylic acid	TWA	NE	NE	NE	NE	NE	5 mg/m ³
	STEL	NE	NE	NE	NE	NE	NE
Modified MDI	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
OSHA TABLE COMMENTS:							
1. NIOSH REL							

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

SKIN: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

RESPIRATORY: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

PROTECTIVE CLOTHING: Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

WORK HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Slight

COLOR: Yellow

pH: Not Applicable

PERCENT VOLATILE: 0.02

VAPOR PRESSURE: < 0.1 mmHg at 25°C (77°F)

VAPOR DENSITY: Heavier than air

BOILING POINT: > 208°C (406°F)

FLASHPOINT AND METHOD: 193°C (380°F) Pensky-Martens CC

SOLUBILITY IN WATER: Reacts slowly with water

SPECIFIC GRAVITY: 1.120 (water=1) at 25°C (77°F)

VISCOSITY: 70 Centipoise at 25°C (77°F)

VOC (Volatile Organic Compound): 0.220 g/l Calculated. Theoretical VOC minus water and exempt solvents.

10. STABILITY AND REACTIVITY

STABILITY: This product is stable under normal ambient conditions of temperature and pressure.

POLYMERIZATION: May occur when exposed to heat in the presence of moisture, alkalies, tertiary amines, metal compounds.

CONDITIONS TO AVOID: High temperatures, moisture, and freezing conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, nitrous oxide, and HCN.

INCOMPATIBLE MATERIALS: Avoid contact with any materials containing active hydrogens such as water, alcohol, amines, bases, and acids.

11. TOXICOLOGICAL INFORMATION**TOXICITY TO ANIMALS**

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
4,4'-Diphenylmethane diisocyanate	> 5000 mg/kg	> 5000 mg/kg	Not Established
1,2-Benzenedicarboxylic acid	> 10 g/kg	> 3.16 g/kg	> 0.13 mg/l
Modified MDI	Not Established	Not Established	Not Established

CARCINOGENICITY

Chemical Name	IARC Status
4,4'-Diphenylmethane diisocyanate	3

12. ECOLOGICAL INFORMATION**AQUATIC TOXICITY**

96-HOUR LC₅₀: > 1000 mg/l Zebra Fish

48-HOUR EC₅₀: > 1000 mg/l Daphnia magna (24 hour)

96-HOUR EC₅₀: > 100 mg/l E.Coli

Notes: This information is based only on MDI and its derivatives.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The generation of waste should be avoided or minimized wherever possible. Disposal should be in accordance with local, state, provincial or national regulations.

EMPTY CONTAINER: Containers must be emptied (as defined by RCRA, 40 CFR Section 261.7 or state regulations that may be more stringent) and either passed to an approved recycler or destroyed.

14. TRANSPORT INFORMATION**DOT (DEPARTMENT OF TRANSPORTATION) LAND**

NOTE: Not Regulated

AIR (ICAO/IATA): Not Regulated

VESSEL (IMO/IMDG): Not Regulated

15. REGULATORY INFORMATION**UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

311/312 HAZARD CATEGORIES: Acute health hazard. Chronic health hazard

313 REPORTABLE INGREDIENTS: This product contains the following substances subject to the reporting requirements

of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt. %	CAS	Comments
4,4'-Diphenylmethane diisocyanate	40 - 50	101-68-8	Diisocyanate Compounds (Category Code N120)

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675).

Chemical Name	Wt. %	CERCLA RQ
4,4'-Diphenylmethane diisocyanate	40 - 50	5,000 lbs.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: This product or its components are listed in or exempt from the TSCA inventory requirements.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR 1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

REGULATIONS

STATE REGULATIONS: California Proposition 65: This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

CALIFORNIA PROPOSITION 65

Chemical Name	Wt. %	Listed
1,2-Benzenedicarboxylic acid	30 - 40	Developmental Toxicity

OSHA HAZARD COMM. RULE: The contents of the MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

16. OTHER INFORMATION

REASON FOR ISSUE: Revised format

APPROVED BY: Michael Rose **TITLE:** R & D Manager


PREPARED BY: Gus Alidad

REVISION SUMMARY: New MSDS

HMIS RATING

HEALTH:	*	2
FLAMMABILITY:		1
PHYSICAL HAZARD:		1
PERSONAL PROTECTION:		X

NFPA CODES



HMIS RATINGS NOTES: Personal Protection: See Section 8

MANUFACTURER DISCLAIMER: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.