

MATERIAL SAFETY DATA SHEET



Date Issued: 03/27/2008
MSDS No: TC-8745 PART A

TC-8745 PART A

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: TC-8745 PART A
GENERAL USE: Polyurethane resin
CHEMICAL FAMILY: Aromatic diisocyanate terminated prepolymer

MANUFACTURER

BJB Enterprises, Inc.
14791 Franklin Avenue
Tustin, CA 92780
Customer Service Number: (714) 734-8450
Fax: (714) 734-8929

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300
or (703) 527-3887

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Pale yellow viscous liquid with a slight odor.

IMMEDIATE CONCERNS: May cause eye and skin irritation. Use in well ventilated areas. Avoid breathing vapors. Avoid contact with strong oxidizers and strong acids, as sudden reaction may result in fire and toxic fumes. Reacts slowly with water to produce carbon dioxide which may rupture containers. This reaction accelerates at higher temperatures.

POTENTIAL HEALTH EFFECTS

EYES: Liquid and vapors are irritating to eyes. May cause severe injury which may not be reversible.

SKIN: May cause irritation and possible allergic sensitivity. Skin inflammation is characterized by itching, scaling, or reddening.

INGESTION: May be harmful if swallowed.

INHALATION: May be harmful if inhaled. Inhalation at levels above the occupational exposure limit could cause respiratory sensitization and risk of serious damage to the respiratory system. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitized persons.

MEDICAL CONDITIONS AGGRAVATED: Asthma and other respiratory disorders.

ROUTES OF ENTRY: Eye and skin contact, inhalation of vapors, or accidental ingestion.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
1,2-Benzenedicarboxylic acid, butyl phenylmethyl ester	5 - 15	000085-68-7
Toluene-2,4-diisocyanate	< 0.1	000584-84-9
Toluene-2,6-diisocyanate	< 0.1	000091-08-7

4. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult a physician.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

INGESTION: If swallowed, call a physician immediately. Do NOT induce vomiting. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

INHALATION: Remove patient from exposure, keep warm and at rest. Obtain immediate medical attention. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is labored, oxygen should be administered by qualified personnel. Apply artificial respiration if breathing has ceased or shows signs of failing.

NOTES TO PHYSICIAN: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: 154°C (310°F) Pinsky-Martens CC

GENERAL HAZARD: Product is neither combustible nor flammable, however, under extreme heat product may undergo decomposition releasing toxic vapors.

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, water or water spray.

HAZARDOUS COMBUSTION PRODUCTS: Hydrogen cyanide, carbon monoxide, carbon dioxide, oxides of nitrogen and isocyanate vapors.

FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

FIRE FIGHTING EQUIPMENT: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

LARGE SPILL: Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

RELEASE NOTES: US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

HANDLING: Use appropriate personal protective equipment as specified in Section 8. Handle in a well ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

STORAGE: Store in a cool, dry place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

SHELF LIFE: 6 months from date of shipment under manufacturers recommended storage conditions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1,2-Benzenedicarboxylic acid, butyl phenylmethyl ester	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
Toluene-2,4-diisocyanate	TWA	NE	NE	0.005	NE	NE	NE
	STEL	NE	NE	0.02	NE	NE	NE
Toluene-2,6-diisocyanate	TWA	NE	NE	0.005	NE	NE	NE
	STEL	NE	NE	0.02	NE	NE	NE

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

SKIN: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

RESPIRATORY: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

PROTECTIVE CLOTHING: Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

WORK HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Viscous liquid

ODOR: Slight

COLOR: Pale yellow

pH: Not Established

PERCENT VOLATILE: 0.5

VAPOR PRESSURE: < 0.1 mmHg

VAPOR DENSITY: Not Established

BOILING POINT: > 200°C (392°F)

FLASHPOINT AND METHOD: 154°C (310°F) Pensky-Martens CC

SOLUBILITY IN WATER: Reacts slowly with water

SPECIFIC GRAVITY: 1.110 (water=1) at 25°C (77°F)

VISCOSITY: 11600 Centipoise at 25°C (77°F)

VOC (Volatile Organic Compound): 5.600 g/l Calculated. Theoretical VOC minus water and exempt solvents.

10. STABILITY AND REACTIVITY

STABILITY: This product is stable under normal ambient conditions of temperature and pressure.

POLYMERIZATION: Product may foam when exposed to heat and moisture.

CONDITIONS TO AVOID: High temperatures, moisture, and freezing conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: Hydrogen cyanide, carbon monoxide, carbon dioxide, oxides of nitrogen and isocyanate vapors.

INCOMPATIBLE MATERIALS: Water, alcohols, amines, strong bases, metal compounds and surfactants may react with evolution of heat and carbon dioxide.

11. TOXICOLOGICAL INFORMATION

TOXICITY TO ANIMALS

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
1,2-Benzenedicarboxylic acid, butyl phenylmethyl ester	20400 mg/kg	> 10000 mg/kg	> 6.7 mg/l
Toluene-2,4-diisocyanate	> 5000 mg/kg	> 4000 mg/kg	> 480 mg/kg
Toluene-2,6-diisocyanate	> 5000 mg/kg	> 4000 mg/kg	> 480 mg/kg

CARCINOGENICITY

Chemical Name	IARC Status
Toluene-2,4-diisocyanate	2B
Toluene-2,6-diisocyanate	2B

IARC: This product contains substances that are classified as possible carcinogens to humans.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The generation of waste should be avoided or minimized wherever possible. Disposal should be in accordance with local, state, provincial or national regulations.

EMPTY CONTAINER: Containers must be emptied (as defined by RCRA, 40 CFR Section 261.7 or state regulations that may be more stringent) and either passed to an approved recycler or destroyed.

14. TRANSPORT INFORMATION**DOT (DEPARTMENT OF TRANSPORTATION) LAND**

NOTE: Not Regulated

AIR (ICAO/IATA)

NOTE: Not Regulated

VESSEL (IMO/IMDG)

NOTE: Not Regulated

15. REGULATORY INFORMATION**UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****311/312 HAZARD CATEGORIES:** None**313 REPORTABLE INGREDIENTS:** This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
None**CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)****CERCLA REGULATORY:** For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675).

Chemical Name	Wt. %	CERCLA RQ
1,2-Benzenedicarboxylic acid, butyl phenylmethyl ester	5 - 15	100 lbs.
Toluene-2,4-diisocyanate	< 0.1	100 lbs.
Toluene-2,6-diisocyanate	< 0.1	100 lbs.

TSCA (TOXIC SUBSTANCE CONTROL ACT)**TSCA STATUS:** This product or its components are listed in or exempt from the TSCA inventory requirements.**CLEAN AIR ACT**

Chemical Name	Wt. %	CAS
Toluene-2,4-diisocyanate	< 0.1	000584-84-9
Toluene-2,6-diisocyanate	< 0.1	000091-08-7

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)**29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS:** None of the chemicals in this product are considered highly hazardous by OSHA.**REGULATIONS****STATE REGULATIONS** California Proposition 65: This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):**CALIFORNIA PROPOSITION 65**

Chemical Name	Wt. %	Listed
1,2-Benzenedicarboxylic acid, butyl phenylmethyl ester	5 - 15	• Developmental Toxicity

OSHA HAZARD COMM. RULE: The contents of the MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

16. OTHER INFORMATION

REASON FOR ISSUE: New Issue


APPROVED BY: Michael Rose **TITLE:** R & D Manager

PREPARED BY: Gus Alidad

HMIS RATING

HEALTH:	1
FLAMMABILITY:	1
PHYSICAL HAZARD:	1
PERSONAL PROTECTION:	X

NFPA CODES



HMIS RATINGS NOTES: Personal Protection: See Section 8

MANUFACTURER DISCLAIMER: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.