

MATERIAL SAFETY DATA SHEET



Date Issued: 05/01/2006
 MSDS No: TC-890 PART B
 Date-Revised: 06/25/2009
 Revision No: 1

TC-890 PART B

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: TC-890 PART B
GENERAL USE: Polyurethane curing agent
CHEMICAL FAMILY: Polyoxyalkylene glycols, plasticizer mixture

MANUFACTURER

BJB Enterprises, Inc.
 14791 Franklin Avenue
 Tustin,, CA 92780
Customer Service Number: (714) 734-8450
Fax: (714) 734-8929

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300
 or (703) 527-3887

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE AND ODOR: White liquid with a slight odor.

IMMEDIATE CONCERNS: Avoid eye and skin contact. Avoid breathing vapors. May cause eye and skin irritation. Use in well ventilated areas.

POTENTIAL HEALTH EFFECTS

EYES: May cause irritation.

SKIN: May cause irritation and possible allergic sensitivity with repeated contact.

INGESTION: May be harmful if swallowed.

INHALATION: May result in respiratory irritation.

MEDICAL CONDITIONS AGGRAVATED: No data is available.

ROUTES OF ENTRY: Eye and skin contact, inhalation of vapors, or accidental ingestion.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Polyoxyalkylene glycols	60 - 80	Proprietary
1,2-Benzenedicarboxylic acid	30 - 40	68515-48-0
Titanium oxide (TiO ₂)	< 1	13463-67-7

4. FIRST AID MEASURES

EYES: Immediately rinse with water. Remove contact lenses. Hold eyelids apart and flush eyes with water for at least 15 minutes. Get immediate medical attention.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

INGESTION: If swallowed, call a physician immediately. Remove stomach contents by gastric suction or induce vomiting only as directed by medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

NOTES TO PHYSICIAN: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: 182°C (360°F) Pensky-Martens CC

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical, or alcohol foam.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, and carbon dioxide.

FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

FIRE FIGHTING EQUIPMENT: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

LARGE SPILL: Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

RELEASE NOTES: US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

HANDLING: Use appropriate personal protective equipment as specified in Section 8. Handle in a well ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

STORAGE: Store in a cool, dry place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

SHELF LIFE: 6 months from date of shipment under manufacturers recommended storage conditions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		SupplierOEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Polyoxyalkylene glycols	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
1,2-Benzenedicarboxylic acid	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
Titanium oxide (TiO ₂)	TWA	NE ^[1]	15 T ^[1]	NE ^[1]	10 ^[1]	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
OSHA TABLE COMMENTS:							
1. Total dust (8 hours)							

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

SKIN: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

RESPIRATORY: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

PROTECTIVE CLOTHING: Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

WORK HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Slight

COLOR: White

pH: Not Established

PERCENT VOLATILE: 0.02

VAPOR PRESSURE: Not Established

VAPOR DENSITY: Not Established

BOILING POINT: Not Established

FLASHPOINT AND METHOD: 182°C (360°F) Pensky-Martens CC

SOLUBILITY IN WATER: Partially Soluble

SPECIFIC GRAVITY: 1.040 (water=1) at 25°C (77°F)

VISCOSITY: 830 Centipoise at 25°C (77°F)

VOC (Volatile Organic Compound): 0.200 g/l Calculated. Theoretical VOC minus water and exempt solvents.

10. STABILITY AND REACTIVITY

STABILITY: This product is stable under normal ambient conditions of temperature and pressure.

POLYMERIZATION: Product will not undergo polymerization.

CONDITIONS TO AVOID: High temperatures, moisture, and freezing conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and carbon dioxide.

INCOMPATIBLE MATERIALS: Isocyanates, oxidizing agents, and strong mineral acids.

11. TOXICOLOGICAL INFORMATION

TOXICITY TO ANIMALS

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Polyoxyalkylene glycols	Not Established	Not Established	Not Established
1,2-Benzenedicarboxylic acid	Not Established	Not Established	Not Established
Titanium oxide (TiO ₂)	> 24000 mg/kg	> 10000 mg/kg	> 6.82 mg/l

CARCINOGENICITY

Chemical Name	IARC Status
Titanium oxide (TiO ₂)	2B

IARC: This product contains substances that are classified as possible carcinogens to humans.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The generation of waste should be avoided or minimized wherever possible. Disposal should be in accordance with local, state, provincial or national regulations.

EMPTY CONTAINER: Containers must be emptied (as defined by RCRA, 40 CFR Section 261.7 or state regulations that may be more stringent) and either passed to an approved recycler or destroyed.

14. TRANSPORT INFORMATION**DOT (DEPARTMENT OF TRANSPORTATION) LAND**

NOTE: Not Regulated

AIR (ICAO/IATA): Not Regulated

VESSEL (IMO/IMDG): Not Regulated

15. REGULATORY INFORMATION**UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

311/312 HAZARD CATEGORIES: Acute health hazard

313 REPORTABLE INGREDIENTS: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
None

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: This product or its components are listed in or exempt from the TSCA inventory requirements.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR 1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

CALIFORNIA PROPOSITION 65: This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):
None

OSHA HAZARD COMM. RULE: The contents of the MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

16. OTHER INFORMATION

REASON FOR ISSUE: Revision

APPROVED BY: Michael Rose **TITLE:** R & D Manager


PREPARED BY: Gus Alidad

REVISION SUMMARY: Revision 1

HMIS RATING

HEALTH:	1
FLAMMABILITY:	1
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	X

NFPA CODES



HMIS RATINGS NOTES: Personal Protection: See Section 8

MANUFACTURER DISCLAIMER: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.