

MATERIAL SAFETY DATA SHEET



Date Issued: 12/08/2011
MSDS No: WC-780 PART A

WC-780 PART A

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WC-780 PART A

GENERAL USE: Polyurethane resin

CHEMICAL FAMILY: Polyglycol, isocyanate terminated/aliphatic diisocyanate mixture

MANUFACTURER

BJB Enterprises, Inc.
14791 Franklin Avenue
Tustin, CA 92780

Customer Service Number: (714) 734-8450

Fax: (714) 734-8929

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300
or (703) 527-3887

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE AND ODOR: Clear colorless liquid with a slight odor.

IMMEDIATE CONCERNS: Harmful if inhaled or swallowed. May cause eye, skin, and respiratory tract irritation. Use in well ventilated areas. Avoid breathing vapors. Avoid contact with strong oxidizers and strong acids, as sudden reaction may result in fire and toxic fumes. Reacts slowly with water to produce carbon dioxide which may rupture containers. This reaction accelerates at higher temperatures.

POTENTIAL HEALTH EFFECTS

EYES: May cause irritation, tearing, reddening, and swelling. May cause slight corneal injury.

SKIN: May cause irritation and possible allergic sensitivity. Skin inflammation is characterized by itching, scaling, or reddening.

INGESTION: Harmful if swallowed. Aspiration hazard. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and damage. It may also cause irritation to the mucous membranes of the mouth, throat, and digestive tract.

INHALATION: Toxic by inhalation of aerosol or mist. If misted, irritation of mucous membranes, nose, eyes, and throat may occur. Extremely high vapor concentrations may cause lung damage. Inhalation at levels above the occupational exposure limit could cause respiratory sensitization and risk of damage to the respiratory system. The onset of the respiratory system may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitized persons.

MEDICAL CONDITIONS AGGRAVATED: May cause or aggravate dermatitis and asthma.

ROUTES OF ENTRY: Eye and skin contact, inhalation of vapors, or accidental ingestion.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Dicyclohexylmethane-4,4'-diisocyanate	75 - 85	5124-30-1
poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro.-omega.-hydroxy-, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane]	15 - 25	9042-82-4

4. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult a physician.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash

WC-780 PART A

clothing before reuse.

INGESTION: If swallowed, call a physician immediately. Do NOT induce vomiting. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

INHALATION: Remove patient from exposure, keep warm and at rest. Obtain immediate medical attention. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is labored, oxygen should be administered by qualified personnel. Apply artificial respiration if breathing has ceased or shows signs of failing.

NOTES TO PHYSICIAN: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: 207°C (405°F) Pinsky-Martens CC

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical, or alcohol foam.

EXPLOSION HAZARDS: Avoid contact with strong oxidizers and strong acids, as sudden reaction may result in fire and toxic fumes. Reacts slowly with water to produce carbon dioxide which may rupture closed containers. This reaction accelerates at higher temperatures.

FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

FIRE FIGHTING EQUIPMENT: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

LARGE SPILL: Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

RELEASE NOTES: US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

HANDLING: Use appropriate personal protective equipment as specified in Section 8. Handle in a well ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

STORAGE: Store in a cool, dry place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

SHELF LIFE: 6 months from date of shipment under manufacturers recommended storage conditions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

WC-780 PART A

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		SupplierOEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Dicyclohexylmethane-4,4'-diisocyanate	TWA	NE	NE	0.005	0.054	0.01 ^[1]	0.11 ^[1]
	STEL	NE	NE	NE	NE	NE	NE
poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-hydroxy-, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane]	TWA	NE	NE	NE	NE	NE	NE
	STEL	NE	NE	NE	NE	NE	NE
OSHA TABLE COMMENTS:							
1. NIOSH REL (ceiling)							

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

SKIN: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

RESPIRATORY: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

PROTECTIVE CLOTHING: Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

WORK HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Slight

COLOR: Colorless

pH: Not Applicable

PERCENT VOLATILE: 0.1

VAPOR PRESSURE: < 0.001 mmHg at 25°C (77°F)

VAPOR DENSITY: Not Established

BOILING POINT: Decomposes

FLASHPOINT AND METHOD: 207°C (405°F) Pensky-Martens CC

SOLUBILITY IN WATER: Insoluble, reacts slowly with water

SPECIFIC GRAVITY: 1.080 (water=1) at 25°C (77°F)

VISCOSITY: 650 Centipoise at 25°C (77°F)

VOC (Volatile Organic Compound): 1.080 g/l Calculated. Theoretical VOC minus water and exempt solvents.

10. STABILITY AND REACTIVITY

WC-780 PART A

STABILITY: This product is stable under normal ambient conditions of temperature and pressure.

POLYMERIZATION: Product may foam when exposed to heat and moisture.

CONDITIONS TO AVOID: High temperatures, moisture, and freezing conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, nitrous oxide, and HCN.

INCOMPATIBLE MATERIALS: Moisture, strong acids, amines, and metal carboxylates.

11. TOXICOLOGICAL INFORMATION**TOXICITY TO ANIMALS**

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Dicyclohexylmethane-4,4'-diisocyanate	9900 mg/kg	> 10000 mg/kg	0.29 to 0.30 mg/l (4 h of aerosols)
poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-hydroxy-, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane]	Not Established	Not Established	Not Established

12. ECOLOGICAL INFORMATION**AQUATIC TOXICITY**

96-HOUR LC₅₀: >= 8.1 mg/l *Brachydanio rerio* (96 hours)

48-HOUR EC₅₀: >= 8.3 mg/l *Daphnia magna*

96-HOUR EC₅₀: >= 5.0 mg/l *Scenedesmus subspicatus* (72 hours)

Notes: This information is based only on the Dicyclohexylmethane-4,4'-diisocyanate.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The generation of waste should be avoided or minimized wherever possible. Disposal should be in accordance with local, state, provincial or national regulations.

EMPTY CONTAINER: Containers must be emptied (as defined by RCRA, 40 CFR Section 261.7 or state regulations that may be more stringent) and either passed to an approved recycler or destroyed.

14. TRANSPORT INFORMATION**DOT (DEPARTMENT OF TRANSPORTATION) LAND**

NOTE: Not Regulated

AIR (ICAO/IATA): Not Regulated

VESSEL (IMO/IMDG): Not Regulated

15. REGULATORY INFORMATION**UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

311/312 HAZARD CATEGORIES: Acute health hazard. Chronic health hazard

313 REPORTABLE INGREDIENTS: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt. %	CAS	Comments
Dicyclohexylmethane-4,4'-diisocyanate	75 - 85	5124-30-1	Diisocyanate Compounds (Category Code N120)

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour

WC-780 PART A

period requires notification to the National Response Center (800-424-8802 or 202-426-2675):

None

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: This product or its components are listed in or exempt from the TSCA inventory requirements.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

CALIFORNIA PROPOSITION 65: This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

None

OSHA HAZARD COMM. RULE: The contents of the MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

CANADA**WHMIS HAZARD SYMBOL AND CLASSIFICATION**

Toxic

Class D-1A: Material causing immediate and serious toxic effects (Very toxic).

Class D-2A: Material causing other toxic effects (Very toxic).

Class D-2B: Material causing other toxic effects (Toxic).

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS CLASS: The D1A classification applies for this material in aerosol or mist form.

DOMESTIC SUBSTANCE LIST (INVENTORY): All components in this product are included on the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

EUROPEAN COMMUNITY**EEC LABEL SYMBOL AND CLASSIFICATION**

"T" - Toxic

RISK PHRASES

R23: Toxic by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R42/43: May cause sensitization by inhalation and skin contact.

SAFETY PHRASES

S1/2: Keep locked up and out of reach of children.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28: After contact with skin, wash immediately with plenty of water and soap.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

16. OTHER INFORMATION

REASON FOR ISSUE: Revised format

APPROVED BY: Michael Rose **TITLE:** R & D Manager


PREPARED BY: Gus Alidad

WC-780 PART A

HMIS RATING

HEALTH	*	3
FLAMMABILITY		1
PHYSICAL HAZARD		1
PERSONAL PROTECTION	X	

NFPA CODES



HMIS RATINGS NOTES: Personal Protection: See Section 8

MANUFACTURER DISCLAIMER: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.